

SLG POSITIVE DISPLACEMENT SPUR GEAR METER

Ideal for measuring paints & coatings, especially where robotics are utilized or when space is limited.



APPLICATIONS

In production environments like the automotive industry, a lot of pressure is on line components. While performing under a variety of harsh, fast-paced conditions, flow meters in particular have to be rugged, accurate, and easy to install.

AW-Lake exceeds these demands with its SLG Series Positive Displacement Flow Meters. These

stainless steel meters feature small, light bodies, perfect for installation on robotic arms and in other tight areas. Flow meter construction incorporates virtually no "dead space," which allows for extremely efficient flush cycles and worry-free color changes.

TECHNICAL SPECIFICATIONS

Measuring Accuracy

± 0.5% over 10:1 turndown with 30cP fluid

Repeatability

± 0.1%

Flow Measuring Range

0.005 to 0.8 gpm
0.02 to 2.0 gpm

Maximum Operating Pressure
up to 2,000 psi

Maximum Fluid Temperature
350°F (180°C)

Ports

Bottom ported through hole or 1/8" BSPP – specify upon ordering

BENEFITS

Strong, Compact Design

The SLG's solid stainless steel construction and compact size make this meter ideal for robotic applications where there is limited space, weight restrictions and vibration from movement.

Simple to Install & Use

These meters are easy to use and install, since there is no need for straight run piping upstream or downstream of the flow meter.

Accurate and Reliable

This meter has the ability to maintain consistent accuracy despite changing viscosity conditions, with accuracy of +0.5% of reading.

Flexible

Meter may be used in applications requiring bi-directional flow, and is offered in two different flow ranges (0.005 to 0.8 gal/min and 0.02 to 2.0 gal/min).

MATERIALS OF CONSTRUCTION

Body	JVS: 316 stainless steel (2,000 psi max)
Gears	Stainless Steel, DIN 1.4122
Seals	JVS: PTFE O-ring
Bearings & Shaft	Tungsten Carbide

RECOMMENDED SENSORS

Sensor Type	Model	Sensor Features
Single sensor	CAPM-30	Intrinsically safe, frequency output (when used with a barrier)
Fiber Optic System (includes the following:)	FOP 30/S	
Fiber optic sensor	FOP-30	Fully isolated optical signal, intrinsic safe
Light-to-frequency converter	OPTV-20	Converts optical output to frequency output
Standard heavy-duty fiber optic cable	Fiber optic cable	Available in 30, 40, 60 & 100 foot lengths

SLG POSITIVE DISPLACEMENT SPUR GEAR METER

Ideal for measuring paints & coatings, especially where robotics are utilized or when space is limited.

METER DATA

Meter Size	Flow Range (GPM)	Impulses/ Gallon	Impulses/ cc	Weight (Lbs / Kg)	Ports	Filtration (microns)	Pressure Rating
JVS-12SLGS	0.005-0.8	52,990	14.0	2.75 / 1.25	1/8" BSPP	120	2,000 psi
JVS-12SLGFS	0.005-0.8	52,990	14.0	2.75 / 1.25	6 mm (not threaded)	120	2,000 psi
JVS-20SLGS	0.02-2.0	15,900	4.2	3.0 / 1.36	1/8" BSPP	120	2,000 psi
JVS-20SLGFS	0.02-2.0	15,900	4.2	3.0 / 1.36	6 mm (not threaded)	120	2,000 psi



A COMMON APPLICATION FOR THE SLG GEAR METER IS IN ROBOTIC PAINT LINES IN THE AUTOMOTIVE INDUSTRY.

Products may be subject to change without notice - Contact factory for the most up-to-date product information.