



| | AWL Part #: (Description) | CBL-DP3-x (Pulse Output) | CBL-DP2-x (Analog + Pulse Output) |
|--------|--------------------------------------|-------------------------------------|--|
| Item # | Description / Wire Color | Connection Type | Connection Type |
| 1 | Female Connector, 5 Pin, M12 Thread | NA | NA |
| 2 | Cable | NA | NA |
| Pin 1 | Red | 12-24 VDC | 12-24 VDC |
| Pin 2 | Black | Ground | Ground |
| Pin 3 | White | Frequency Out 1 | Current Out |
| Pin 4 | Green | Frequency Out 2 | Voltage Out |
| Pin 5 | Brown | N/C | Frequency Out 1 |



2440 W Corporate Preserve Dr #600
Oak Creek, WI 53154
Phone: 414.574.4300
Fax: 414.574.4301

UNITS: INCHES

TOLERANCES UNLESS OTHERWISE NOTED
INCHES METRIC
.XXX ± .0005 .XXX ± .013
.XX ± .003 .XX ± .07
.X ± .01 .X ± .25
FRAC. ± 1/64 ANG. ± 5°



Surface Roughness [Ra]: 64µin / 1.6µm

DRAWING NO.: CBL-DPx-x

PART NO.:
CBL-DPx-x

PART NO. (Legacy): NA

PART NO. (Supplier): NA

MATERIAL: NA

DESCRIPTION:

Edge Sensor_Cable_Pulse Output & Analog + Pulse Output

Cert. Controlled: No

Cert. Type:

SCALE: 1:1

SHEET: 1 OF 1

SIZE: A

REV: **A**

Status:
Released

DRAWN BY:
SH

DATE:
3/31/2022

MODELED BY:
S. Honsberger

DATE:
3/31/2022

| REV. | DATE | BY | DESCRIPTION | APPR. BY | DATE | ECN No. |
|------|-----------|----|-------------------------|----------|-----------|---------|
| A | 3/31/2022 | SH | Initial Drawing Release | SH | 3/31/2022 | |

REVISIONS